

LIGHTRAIL

Illuminated Handrail



Illinois Governor's Mansion
Springfield, IL

LR7 & LR8

Cole Lightrail™ systems are versatile and functional illuminated handrails, suitable for exterior or interior stair, ramp or guardrail applications. Lightrail™ is available in symmetrical and asymmetrical light distribution patterns, projecting light where it is needed. Lightrail™ may be wall or post mounted with integral or remote power supplies. Additionally, mounting provisions may be furnished for coordination with another railing manufacturer—such as for the attachment to a guardrail. Matching non-illuminated railings are also offered for each series. Cole Lightrail™ is specifically designed and fabricated for each installation. Lightrail™ is designed and engineered to withstand the abuse typical in public areas. The high impact acrylic diffusers are regressed within heavy duty stainless steel or extruded aluminum housings. All rails are seam-welded and ground smooth allowing one-piece, seamless construction. Modified or custom illuminated railings can be developed to your exact specifications. Cole Lightrails™ are Underwriters' Laboratories (cULus) listed for use in wet locations. Design features comply with the Americans with Disabilities Act (ADA) and other applicable codes. To learn more about our custom capabilities and comprehensive range of standard lighting fixtures, call us or your local Cole representative.




C.W. Cole & Company, Inc.
2560 Rosemead Boulevard
South El Monte, CA 91733-1593


Tel. (626) 443-2473
Fax (626) 443-9253
info@colelighting.com
www.colelighting.com

LR7 & LR8 - LED


LR7




LR8



Dimensions



Symmetric 90°



Standard Caprail Materials

Painted Aluminum or Steel



Bronze

Aluminum


Steel

Standard Mounts


Direct Burial



Wall Mount



Baseplate Mount



Catalog Number

Post mounted, remote driver
 Wall mounted, remote driver
 Post mounted, remote driver
 Wall mounted, remote driver

Aluminum (-AL)

LR7P -LED-AL-REM
 LR7W-LED-AL-REM
 LR8P -LED-AL-REM
 LR8W-LED-AL-REM

Malleable Steel (-STL)

LR7P -LED-STL-REM
 LR7W-LED-STL-REM
 LR8P -LED-STL-REM
 LR8W-LED-STL-REM

Bronze (-BZ)

LR7P -LED-BZ-REM
 LR7W-LED-BZ-REM
 LR8P -LED-BZ-REM
 LR8W-LED-BZ-REM

Options

Caprail Ends: by Julius Blum®

Square End Piece. Add suffix **-SQ**,
 Straight Lambs Tongue. Add suffix **-LT**,
 Volute. Add suffix **-V**.

Frosted lens: (clear diffuser is std.). Add suffix **-FL**.

4000°K Color temperature: (3000°K standard.).
 Add suffix **-4K**.


Escutcheon/Base: by Julius Blum® 3" by 3" sq. decorative base for direct burial post. Add suffix **-ES**.

Baseplate: 5" square baseplate + four mounting holes.
 Add suffix **-BP**.

Dimming: Universal voltage 0-10V driver. Add suffix **-DIM**


Emergency battery: Provides up to 90 min. of operation.
 Add suffix **-EM**.

Custom Color: RAL Powder-Coat, consult with factory
 Add suffix **-CC**



LR5 & LR6 Lightrail Brochure

Measurement Instructions Booklet



Volute (-V)




Square End Piece (-SQ)




Straight Lamb Tongue (-LT)

LR7 & LR8 - ZETA750S Puck


LR7-PK




LR8-PK




Dimensions








Symmetric 105°



Symmetric 70°



Asymmetric 75°



Alphabet Zeta750S Literature

8 page
Spec. Sheet
PDF

Catalog Number	Aluminum (-AL)	Malleable Steel (-STL)	Bronze (-BZ)
Post mounted, remote driver	LR7P -PK-AL-REM	LR7P -PK-STL-REM	LR7P -PK-BZ-REM
Wall mounted, remote driver	LR7W-PK-AL-REM	LR7W-PK-STL-REM	LR7W-PK-BZ-REM
Post mounted, remote driver	LR8P -PK-AL-REM	LR8P -PK-STL-REM	LR8P -PK-BZ-REM
Wall mounted, remote driver	LR8W-PK-AL-REM	LR8W-PK-STL-REM	LR8W-PK-BZ-REM



Options

Caprail Ends: by Julius Blum®

Square End Piece. Add suffix **-SQ**,
Straight Lambs Tongue. Add suffix **-LT**,
Volute. Add suffix **-V**.

Puck Beam spread: (105° standard).

70°, Add suffix **-70°**.

Asymmetric 75°, Add suffix **-ASYM/75°**.

Dimming: Universal voltage 0-10V driver.

Add suffix **-DIM**

Escutcheon/Base: by Julius Blum® 3" by 3" sq.
decorative base for direct burial post. Add suffix **-ES**.

Baseplate: 5" square baseplate + four mounting
holes. Add suffix **-BP**.


Frosted lens: (clear diffuser standard). Add suffix **-FL**.

4000°K Color temperature: (3000°K standard).


Add suffix **-4K**.

Emergency battery: Provides up to 90min. of
operation. Add suffix **-EM**.

Custom Color: RAL Powder-Coat, consult with
factory. Add suffix **-CC**



Volute
(-V)



Square
End Piece
(-SQ)



Straight
Lamb Tongue
(-LT)




LIGHTRAIL

Decorative
Illuminated
Handrail

CUSTOM Applications

Museum of the American Revolution - Philadelphia, PA



Illinois Governor's Mansion - Springfield, IL



University of Michigan Hill Auditorium - Ann Arbor, MI

