

SC180 Series



20" dia, x 7-1/2" H (508 x 191mm)

SC180-LED illustrated
with options:

Finish Color **-ABZ**

Example: SC180-LED-ABZ

Construction

- Fixture is 20 gauge steel • Diffusers are .125" white acrylic; other colors, textures, and materials are available • Finish is textured powder coat polyester • Wood accents are stained golden oak unless otherwise specified

Electrical

- Integral universal voltage drivers with optional 0-10v dimming (Dimming down to 1%) • LED options include E26/medium base, standard output and high output modules • 120V-277V electronic drivers are standard universal voltage.

How to Specify

1. Select catalog number with option suffix(es).
2. Specify color of finish.
3. Consult your Cole representative for other design changes for your requirements.

Catalog Number

Surface Ceiling	Lamps
LED 25W, (2646 lm @ 3000°K)	SC180-LED
LED 50W, (5292 lm @ 3000°K)	SC180-LED/HO
E26 medium base	SC180-LED/E26 (4 sockets)

Lumens shown are source. Church light photometric data available upon request.

Options

Decorative Banding: Adds detailed appearance. Add suffix **-DB**.

Metal Channel Accents: Provides steel side channels in lieu of wood. Add suffix **-MCA**.

Delete Wood Accents: Add suffix **-DWA**.

Finish Color:

Antique Bronze Vein: Add suffix **-ABZ**.

Antique Copper Vein: Add suffix **-ACP**.

Diffusers: Alternates to standard white acrylic.

Clear sandblasted acrylic: Add suffix **-ACR**.

Other shielding. Add suffix **-OS/** specify.

LED colors:

2700°K (7807 lm), HO (24489 lm) Add suffix **-27K**.

4100°K (11710 lm), HO (36734 lm) Add suffix **-4K**.

Dimming: Universal voltage, 0-10V driver.

1%-100% range. Add suffix **-DIM**.

COLE
Lighting

C.W. Cole & Company, Inc.
2560 Rosemead Boulevard
South El Monte, CA 91733-1593

Tel. (626) 443-2473

Fax (626) 443-9253

info@colelighting.com

www.colelighting.com