

JOB NAME _____

TYPE _____

CATALOG NUMBER _____

*Gothic
illustrated*



Hexagon
24" across points x 9 -1/2"
H (610 x 241mm)

SC160-LED illustrated
with options:
Gothic Design **-GTH**
Decorative Banding **-DB**
Flared Tips **-FT**
Finish Color **-ABZ**
Diffusers **-ACR**

Example:
SC160-LED-GTH-DB-FT-ABZ-ACR

*Romanesque
illustrated*



SC160-LED illustrated
with options:
Romanesque Design **-ROM**
Finish Color **-ACP**
Diffusers **-GLS**

Example:
SC160-LED-ROM-ACP-GLS

**Church Lights
SC160 SERIES**

Specifications

Construction

- Fixture is 20 gauge steel • Diffusers are .125" white acrylic; other colors, textures, and materials are available • Finish is textured powder coat polyester

Electrical

- Integral universal voltage drivers with optional 0-10v dimming (Dimming down to 1%) • LED options include E26/medium base, standard output and high output modules • 120V-277V electronic drivers are standard universal voltage.

How to Specify

1. Select catalog number with option suffix(es).
2. Specify color of finish.
3. Consult your Cole representative for other design changes for your requirements.

Catalog Number

Surface Ceiling	Lamps
LED 25W, (2646 lm @ 3000°K)	<input type="checkbox"/> SC160-LED
LED 50W, (5292 lm @ 3000°K)	<input type="checkbox"/> SC160-LED/HO
E26 medium base	<input type="checkbox"/> SC160-LED/E26 (4 sockets)

Lumens shown are source. Church light photometric data available upon request.

Options

Decorative Banding: Adds detailed appearance.

Add suffix **-DB**.

Flared Tips: Provides extended and flared corner angles.

Add suffix **-FT**.

Romanesque Design: Provides round arch.

Add suffix **-ROM**.

Gothic Design: Provides peaked arch.

Add suffix **-GTH**.

Finish Color:

Antique Bronze Vein. Add suffix **-ABZ**.

Antique Copper Vein. Add suffix **-ACP**.

Diffusers: Alternates to standard white acrylic.

Clear sandblasted acrylic. Add suffix **-ACR**.

Clear sandblasted glass. Add suffix **-GLS**.

Sandblasted "seedy" glass (Recommended for E26 lamps only). Add suffix **-SDY**.

Other shielding. Add suffix **-OS/** _____ *specify*

LED colors:

2700°K (7807 lm), HO (24489 lm). Add suffix **-27K**.

4100°K (11710 lm), HO (36734 lm). Add suffix **-4K**.

Dimming: Universal voltage, 0-10V driver.

1%-100% range. Add suffix **-DIM**.



C.W. Cole & Company, Inc.
2560 Rosemead Boulevard
South El Monte, CA 91733-1593

Tel. (626) 443-2473

Fax (626) 443-9253

info@colelighting.com

www.colelighting.com